IN THE CLAIMS

Page 6, line 1, change "CLAIMS" to -- What is claimed is:--.

Claims 1-13 (cancelled).

14. (New). A wireless microphone system comprising:

antennae connected thereto;

a circulator and/or an HF isolator being connected to the antennae or the antenna; and said circulator and/or HF isolator being integrated in the antenna and the two forming a mechanical unit.

- 15. (New) The wireless microphone system wherein said circulator and/or HF isolator is integrated in the antenna by being plugged in or screwed on.
- 16. (New) The wireless microphone system as set forth in claim 14, wherein the wireless microphone comprises a hand transmitter microphone or a pocket transmitter microphone and a (diversity) receiver.
- 17. (New) The wireless microphone system as set forth in claim 14, wherein the circulator/HF isolator is integrated in the antenna (which can be plugged in or screwed on) and the two form a mechanical unit.
- 18. (New) A pocket transmitter microphone as set forth in claim 16, wherein the antenna provided with the circulator/HF isolator is pluggably connected to the transmitting device of the microphone and that the antenna, circulator/HF isolator and plug device form a mechanical unit.
- 19. (New) A hand transmitter microphone as set forth in claim 16, wherein the antenna which is mechanically fixedly connected to the circulator/HF isolator is disposed in a common housing and is replaceable as a unit.

- 20. (New) The microphone as set forth in claim 14, wherein the pluggable or replaceable antenna-circulator/HF isolator unit is tuned to a given frequency range.
- 21. (New) The wireless microphone device wherein the receiving device also has in its high frequency input a circulator/HF isolator.
- 22. (New) The wireless microphone system as set forth in claim 21, wherein the receiving antenna is fixedly connected to a circulator/HF isolator.
- 23. (New) The wireless microphone system as set forth in claim 21, wherein the receiving antenna with the circulator/HF isolator is at least partially disposed in a common housing.
- 24. (New) The wireless microphone system as set forth in claim 21, wherein the receiver carried on the body is provided with a pluggable or replaceable antennacirculator/HF isolator unit.
- 25. (New) The wireless microphone system as set forth in claim 21, wherein the antenna-circulator/HF isolator unit is tuned to a given frequency range.
 - 26. (New) An HF transmitter comprising:

an antenna connected thereto, said antenna being in accordance with claim 14 and being integrated into or connected to a circulator and/or an HF isolator.

27. (New) The HF transmitter or system as set forth in claim 26, wherein the antenna externally includes a visible identification, coding or color marking or the like, the identification, coding or color marking being attributed to a given frequency range.